



Fabris Dott. Ing. Pasquale srl








Riva 4 Novembre, 9

35013 Cittadella (PD)

tel: +39 049 940 24 36

produzione@fabris1926.it

Dati tecnici Valvole a Inversione Ciclo

modello	100XR	150XR	200XR	300XR	400XR	500XR	600XR
							
A (mm)	170,0	198,0	287,3	322,8	393,8	496,8	592,0
B (mm)	247,0	259,0	285,8	305,0	483,0	485,5	485,5
C (mm)	97,0	109,0	133,8	155,0	200,0	243,0	268,0
n° 1 attacco x rame	ø=35	ø=42	ø=54	ø=64	ø=76	ø=89	ø=108
n° 3 attacchi x rame	ø=35	ø=42	ø=54	ø=76	ø=89	ø=108	ø=133
prese di carico							
1/4"-1/4" SAE	•	•	•	•			
1/4" SAE					•	•	•
3/8" SAE	•	•	•	•	•	•	•
prese su flange							
3/8" NPT	•	•	•	•	•		
1/2" NPT						•	•
pressione max (bar)	50	50	50	50	50	50	50
temperatura max (°C)	150	150	150	150	150	150	150
test in pressione	•	•	•	•	•	•	•
ok prova idrostatica (bar)	150	150	150	150	150	150	150
massa (kg)	7	10	22	30	64	104	144